



Pre-Insulated Flexible Hose Kits

Each Kit Includes

- 2 x Flexible Hose with weatherproof PVC-coated Insulation
- Rubber Washers

Product Features

- Available in the following lengths: 300mm, 500mm, 750mm, and 1000mm
- 28mm Bore and Stainless Steel Overbraid
- 1" or 1-1/4" BSP Female or Male Connection
- 19mm wall thickness PVC coated Insulation
- Complies with Microgeneration Installation Standard 3005

Product Information

Made in compliance with MIS 3005 standards, our flexible hoses simplify connecting flow and return pipes to heat pumps or biomass boilers. These hoses dampen vibrations and enable smooth bends during installation.

They feature a 28mm inner hose encased in a protective stainless steel braid. For easy connection, one end has a male or female BSP thread, while the other uses a 28mm compression fitting. All hoses come pre-insulated with a durable 19mm thick PVC coating that resists weather and UV rays.

Product Code	Description
F128500	Flexible Air Source Heat Pump Hose Pair - 500mm Length - 28mm Bore - 19mm Insulation - 1" Female BSP
F128750	Flexible Air Source Heat Pump Hose Pair - 750mm Length - 28mm Bore - 19mm Insulation - 1" Female BSP
F1281000	Flexible Air Source Heat Pump Hose Pair - 1000mm Length - 28mm Bore - 19mm Insulation - 1" Female BSP
F1E28300	Flexible Air Source Heat Pump Hose Pair - 300mm Length - 28mm Bore - 19mm Insulation - 1" Female BSP - Elbow
F1E28750	Flexible Air Source Heat Pump Hose Pair - 750mm Length - 28mm Bore - 19mm Insulation - 1" Female BSP - Elbow
F11/4E28300	Flexible Air Source Heat Pump Hose Pair - 300mm Length - 28mm Bore - 19mm Insulation - 1-1/4" Female BSP - Elbow
F11/4E28750	Flexible Air Source Heat Pump Hose Pair - 750mm Length - 28mm Bore - 19mm Insulation - 1-1/4" Female BSP